



IP Fisheye 360 Camera CIPF6IR27



- 6MP CMOS 3072 x 2048 resolution
- 18 live display modes
- Smart IR illumination
- 15 m illumination distance
- 1.27 mm fixed lens
- Built in Mic and speaker
- IP67, IK10 12VDCP



Category	Specification
Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Min. Illumination	Color: 0.047 Lux @ (F2.6, AGC On), B/W: 0.0047 Lux @ (F2.6, AGC On), 0 Lux with IR
Shutter Speed	1 sec. to 1/100,000 sec.
Slow Shutter	Yes
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	Digital WDR
Lens	
Focal Length	1.27 mm
Aperture	F2.6
Field of View (FOV)	Horizontal 180° (wall mount); 360° (ceiling mount or table mount)
Lens Mount	M12
IR	
IR Range	Up to 50 ft (15 m) IR range, 3 LEDs. Each LED is independently controlled.
Wavelength	850 nm
Compression Standards	
Video Compressions	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265 / H.264 / MJPEG
H.264 Type	Baseline Profile / Main Profile / High Profile
H.264+	Main stream supported
H.265 Type	Main Profile
H.265+	Main stream supported
Video Bit Rate	32 Kbps to 16 Mbps
SVC	H.265 and H.264 supported

Smart Features	
Behavior Analyses	Line crossing, intrusion, region entrance, region exiting, unattended baggage, & object removal detections
Exception/Anomaly Detection	Audio
Region of Interest	4 fixed regions for main stream and sub-stream
Image	
Max. Resolution	3072 × 2048
Main Stream Max. Frame Rate	50 Hz: 25 fps (3072 × 2048, 2048 × 2048, 1280 × 1280) 60 Hz: 30 fps (3072 × 2048, 2048 × 2048, 1280 × 1280)
Max. Sub Stream Frame Rate	50 Hz: 25 fps (720 × 720, 720 × 480) 60 Hz: 30 fps (720 × 720, 720 × 480)
Image Enhancement	BLC, HLC, defog, 3D DNR
Image Setting	Saturation, brightness, contrast, sharpness, AGC and white balance are adjustable by client software or web browser
Day / Night Switch	Day / Night / Auto / Schedule / Triggered by Alarm In (-S)
Picture Overlay	LOGO picture can be overlaid on video with 128 × 128 24-bit .bmp format

Live View Display	
Mount Type	Table, wall, and ceiling options
Decoding Mode	Supports hardware and software decoding
Display Modes (18)	<p>Ceiling: Fisheye view, 180 panorama view, 360 panorama view, 360 panorama + PTZ, 360 panorama + 3 PTZ, 360 panorama + 6 PTZ, 360 panorama + 8 PTZ, 2 PTZ, 4 PTZ, fisheye + 3 PTZ, fisheye + 8 PTZ, half sphere, cylinder</p> <p>Wall: fisheye view, panorama view, panorama + 3 PTZ, panorama + 8 PTZ, 4 PTZ, fisheye + 3 PTZ, fisheye + 8 PTZ</p> <p>Table: Fisheye view, 180 panorama view, 360 panorama view, 360 panorama + PTZ, 360 panorama + 3 PTZ, 360 panorama + 6 PTZ, 360 panorama + 8 PTZ, 4 PTZ, fisheye + 3 PTZ, fisheye + 8 PTZ, cylinder</p> <p>Hardware decoding: Ceiling: Fisheye view, 180 panorama view, panorama view, 4 PTZ, fisheye + 3PTZ, 4 PTZ fusion</p> <p>Wall: Fisheye view, 180 panorama view, panorama view, 4 PTZ, fisheye + 3 PTZ, 4 PTZ fusion</p> <p>Table: Fisheye view, 180 panorama view, panorama view, 4PTZ, fisheye + 3 PTZ, 4 PTZ fusion</p>
Audio	
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz / 16 kHz
Audio Compression	G.711 / G.722.1 / G.726 / MP2L2 / PCM
Audio Bit Rate	64 Kbps (G.711) / 16 Kbps (G.722.1) / 16 Kbps (G.726) / 32-160 Kbps (MP2L2)

Network	
Network Storage	Supports MicroSD / SDHC / SDXC card (256 GB), local storage and NAS (NFS, SMB / CIFS), ANR
Alarm Triggers	Motion detection, video tampering alarm, network disconnected, IP address conflicted, illegal login, HDD full, HDD error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
Security Measures	Password protection, HTTPS encryption, IEEE 802.1x port-based network access control, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for ONVIF
General Functions	One-key reset, anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter
API	ONVIF (PROFILE S, PROFILE G), ISAPI
Simultaneous Live View	Up to 20 channels
User / Host	Up to 32 users; 3 user levels, administrator, operator and user
Web Browser	Internet Explorer 8+, Chrome 31.0 - 44, Firefox 30.0 - 51, Safari 8.0+
Interface	
Communication Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet port
Audio	1 Audio input (line in, 3.5 mm), 1 audio output (line out, 3.5 mm); 2 built-in microphones, 1 built-in speaker, mono sound
Alarm	1-ch alarm input, max. 12 V; 1-ch alarm output, max. 24 VDC, 1 A
On-board storage	Built-in MicroSD / SDHC / SDXC slot, up to 256 GB
Reset Button	Yes

General	
Operating Conditions	-40° to 140° F (-40° to 60° C), Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 20%, PoE (802.3 af, class 0), two-core terminal block
Power Consumption	12 VDC, 0.9 A, max. 11 W PoE (802.3 af, 36 to 57 V), 0.3 A to 0.2 A, max. 12 W
Protection Level (-V)	IP67, IK10
Material	Metal
Dimensions	φ 6.6 × 2.0 in. (φ 167.4 × 49.9 mm)
Weight	Approx. 2.97 lbs (1,347 g)
Accessories	
Angled Ceiling Mount	RFB755
Wall Mount Bracket	RFB756
Pendant Mount	RFB759